



RELIABILITY IN EVERY REVOLUTION

HVAC



BELTS

CROSS

Dura-Prime ClassicalA, B, 4L, 5L

Dura-Extreme ClassicalAX, BX

Dura-Prime Wedge3V, 5V

Dura-Extreme Wedge3VX, 5VX

Dura-Link 3L, A, B

FEATURES

Quality belts resulting in reduced downtime & maintenance costs

Resistant to oil, heat, moisture, and steam

Superior flexing, enhanced grip for moist conditions

Resistant to hardening and glazing

High strength polyester or aramid cord

Durable advanced rubber compound

ELITE line available featuring EPDM rubber



USES

Air filtration systems

Air handling units

Cooling towers

Air exchangers

Water chillers

Exhaust fans

Scan for
more information!





RELIABILITY IN EVERY REVOLUTION

Why D&D for HVAC?

BECAUSE TESTING PROVES OUR BELTS ARE THE BEST!

In independent testing conducted by the Akron Rubber Development Laboratory, Inc.*, D&D belts outperformed Gates and Browning belts in break force strength by an average of 17% - 34.7%, and within an average of 1.16% - 3% in elongation.

This clearly shows our belts not only match but often exceed the quality of those from an industry leader, and are offered at a more competitive price thanks to our vertical integration manufacturing process.

It's a win-win for both our partners and their customers.

* Independent testing results available upon request

** Additional fees assessed for emergencies.

Our Vertical Integration Process Ensures Superior Quality & Value

By manufacturing our own cord and fabric, owning rubber tree plantations and belt molds, and mixing chemicals to create our own compounds we eliminate reliance on external manufacturers for essential materials. This guarantees top quality belts and eliminates inflated pricing.

TOP SALES & SUPPORT

- Over 60 sales & customer service reps
- Phones answered by real people
- Online inventory search & order portal
- Quick response times
- Midwest nice

LOCATIONS



98%

Orders ship
same day

165,000 sq ft

Total warehouse space

18+

Months of
inventory in stock

35,000+

Unique SKU's

877.784.9267
SALES@DDGLOBAL.COM

DDGLOBAL.COM

2672 ROCK RIDGE DR.
ROCK VALLEY IA, 51247

Testing Results

BX85E

Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	8.61	3003
Browning	7.51	2816.4

AX50E

Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	6.85	1814.43
Browning	7.59	1922

B97

Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	8.90	2980
Browning	8.36	3193.18

3VX670E

Manufacturer	Maximum Elongation, %	Breaking Strength, lbf
D&D	8.03	1747.6
Browning	4.31*	742

* Low elongation is a result of premature breaking before elongation could occur

Our Global Partners Who Trust D&D:



BOSCH



Electrolux

Nestlé

